

*99% of all Moisture Can Be Removed*

**AIR DRYER**

Part No.	Port Size (F) NPT	Air Flow SCFM
12.3120	1/4	10.5
12.3130	3/8	26
12.3140	1/2	53
12.3160	3/4	77
12.3170	1	123
12.3180	1-1/2	212
12.3190	2	424



**REPLACEMENT PARTS (ELEMENT)**

Part No.	Port Size (F) NPT
12.3220	1/4
12.3230	3/8
12.3240	1/2
12.3260	3/4
12.3270	1
12.3280	1-1/2
12.3290	2

**BRACKET**

Part No.	Port Size (F) NPT
12.3320	1/4
12.3330	3/8
12.3340	1/2
12.3360	3/4
12.3370	1
12.3380	1-1/2
12.3390	2

**Applications**

- Perfect for sandblasting, painting or any other application that requires clean and dry air.

**Features**

- 99% of all moisture can be removed.
- Lightweight, compact and easy to install.
- The element is made of a special resin material which provides uninterrupted service.
- Always install a filter upstream of the dryer.
- Built-in auto drain allows for long periods of continuous operation.

**Specifications**

**Maximum Working Pressure**

145 PSI

**Working Temperature**

5°C to 60°C (40°F to 140°F)

**WARNING**

Always install a filter upstream of the air dryer.

**PERFECT FOR SANDBLASTING**

