


BLUE, TRANSPARENT BLUE AND RED

4" AND 20" TAILS

125 PSI



### Applications

- Ideal for compressed air, hydraulics, gas, water, and vacuum
- For assembly lines, paint shops, production equipment, workstations, automotive maintenance shops and construction sites

### Features

- Excellent recoil memory and kink resistance
- Light and flexible for maximum safety and ergonomcy at the workstation
- Oil and abrasion resistant
- Swivel fittings mounted at each end
- 4" and 20" tails

### Specifications

#### Maximum Working Pressure

125 PSI

#### Working Temperature

-40°C to 77°C (-40°F to 170°F)

#### Material

Polyurethane

#### Colours

Blue, Transparent Blue, and Red

### 1/4" I.D. HOSE – ASSEMBLY WITH SWIVEL FITTINGS

BLUE WITH SLEEVE Part No.	RED Part No.	Overall Length ft	Reusable Swivel Fittings
46.4415	46.6415	15	1/4 (M) NPT
46.4420	46.6420	20	1/4 (M) NPT
46.4425	46.6425	25	1/4 (M) NPT
46.4430	46.6430	30	1/4 (M) NPT
46.4450	46.6450	50	1/4 (M) NPT

### 5/16" I.D. HOSE – ASSEMBLY WITH SWIVEL FITTINGS

BLUE WITH SLEEVE Part No.	Overall Length ft	Reusable Swivel Fittings
46.4515	15	1/4 (M) NPT
46.4520	20	1/4 (M) NPT
46.4525	25	1/4 (M) NPT
46.4530	30	1/4 (M) NPT
46.4550	50	1/4 (M) NPT

### 3/8" I.D. HOSE – ASSEMBLY WITH SWIVEL FITTINGS

BLUE WITH SLEEVE Part No.	RED Part No.	Overall Length ft	Reusable Swivel Fittings
46.4615		15	3/8 (M) NPT
46.4616		15	1/4 (M) NPT
46.4620		20	3/8 (M) NPT
46.4621		20	1/4 (M) NPT
46.4625	46.6625	25	3/8 (M) NPT
46.4626	46.6626	25	1/4 (M) NPT
46.4630		30	3/8 (M) NPT
46.4631		30	1/4 (M) NPT
46.4650	46.6650	50	3/8 (M) NPT
46.4651	46.6651	50	1/4 (M) NPT

### 1/2" I.D. HOSE – ASSEMBLY WITH SWIVEL FITTINGS

BLUE Part No.	Overall Length ft	Reusable Swivel Fittings
46.4660	15	1/2 (M) NPT
46.4665	20	1/2 (M) NPT
46.4670	25	1/2 (M) NPT
46.4675	30	1/2 (M) NPT
46.4680	50	1/2 (M) NPT

### REUSABLE BRASS SWIVEL FITTINGS

#### Features

- Full flow male swivel fitting
- Easy to install
- Pre-coated with Teflon

Part No.	Hose I.D. in.	Reusable Swivel Fittings
46.9145	1/4	1/4 (M) NPT
46.9154	5/16	1/4 (M) NPT
46.9164	3/8	1/4 (M) NPT
46.9166	3/8	3/8 (M) NPT
46.9177	1/2	1/2 (M) NPT

