

## 5/16" BAND WIDTH

Part No. Zinc Plated Steel Screw	Part No. Stainless Steel Screw	Minimum Size Dia (in.)	Nominal Size Dia (in.)	Maximum Size Dia (in.)
39.1104	39.1304	5/16	1/4	5/8
39.1106	39.1306	7/16	3/8	7/8

## 1/2" BAND WIDTH

Part No. Zinc Plated Steel Screw	Part No. Stainless Steel Screw	Minimum Size Dia (in.)	Nominal Size Dia (in.)	Maximum Size Dia (in.)
39.1206	39.1406	3/8	7/16	7/8
39.1208	39.1408	7/16	1/2	1
39.1210	39.1410	9/16	5/8	1 1/16
39.1212	39.1412	9/16	3/4	1 1/4
39.1216	39.1416	11/16	1	1 1/2
39.1220	39.1420	3/4	1 1/4	1 3/4
39.1224	39.1424	1 1/16	1 1/2	2
39.1228	39.1428	1 5/16	1 3/4	2 1/4
39.1232	39.1432	1 9/16	2	2 1/2
39.1236	39.1436	1 13/16	2 1/4	2 3/4
39.1240	39.1440	2 1/16	2 1/2	3
39.1242	39.1442	2-5/16	2-3/4	3-1/4
39.1244	39.1444	2-9/16	3	3-1/2
39.1246	39.1446	2-13/16	3-1/4	3-3/4
39.1248	39.1448	3-1/16	3-1/2	4
39.1250	39.1450	3-5/16	3-3/4	4-1/4
39.1252	39.1452	2-1/2	3-1/2	4-1/2
39.1254	39.1454	3	4	5
39.1256	39.1456	3-1/2	4-1/2	5-1/2
39.1258	39.1458	3-3/4	4-3/4	5-3/4
39.1260	39.1460	4	5	6
39.1262	39.1462	4-1/2	6	6-1/2
39.1264	39.1464	5	6-1/2	7
39.1266	39.1466	5-3/4	7	7-3/4
39.1268	39.1468	6-1/2	8	8-1/2
39.1270	39.1470	2	6	10
39.1272	39.1472	1-3/4	6-1/4	10-3/4
39.1274	39.1474	2-1/16	7-3/16	12-1/4
39.1276	39.1476	11	12-1/2	13
39.1278	39.1478	11-3/4	13-1/4	13-3/4
39.1280	39.1480	12-1/2	14	14-1/2
39.1282	39.1482	13-1/4	14-3/4	15-1/4



### Applications

- Ideal for rubber or thermoplastic hoses
- To be used with hose barb fittings

### Features

- Ensures completely leakproof connections
- Narrow, compact and easy to install in hard to reach areas
- Plated steel or stainless steel screw
- Excellent resistance to corrosion



**For any questions  
or information about  
compressed air  
you may contact us at  
Tel. : 1-888-730-0501  
Fax : 1-888-730-3522  
or visit our web site at  
[www.airmax.ca](http://www.airmax.ca)**



### Applications

- Ideal for natural or synthetic rubber and thermoplastic hoses with hose barb fittings
- For industrial hose maintenance and OEM applications on air, fluid, gas and steam lines
- Recommended for high vibration equipment and low pressure hydraulic applications

### Features

- One-piece zinc plated steel design
- Assures adequate closure and compensates for tolerance variations in hose sizes
- Spring like action that does not damage hoses

### 2-EAR CLAMP

Part No.	Model	Closed Size po.	Nominal Size in.	Opened Size in.
39.2200	4.1	0.122	5/32	0.161
39.2201	4.55	0.138	11/64	0.177
39.2202	5	0.118	3/16	0.197
39.2204	7	0.197	1/4	0.276
39.2208	9	0.276	5/16	0.354
39.2211	11	0.315	3/8	0.433
39.2216	13	0.433	1/2	0.512
39.2219	15	0.512	9/16	0.591
39.2222	17	0.591	19/32	0.669
39.2224	18	0.591	5/8	0.708
39.2227	20	0.669	3/4	0.787
39.2229	22	0.748	13/16	0.866
39.2230	23	0.787	7/8	0.905
39.2232	25	0.866	15/16	0.984
39.2234	27	0.905	1	1.063
39.2235	28	0.984	1 1/16	1.102
39.2237	31	1.063	1 1/8	1.220
39.2241	34	1.220	1 5/16	1.339
39.2243	37	1.339	1 7/16	1.457
39.2245	40	1.457	1 1/2	1.575
39.2247	43	1.575	1 5/8	1.693
39.2249	46	1.693	1 3/4	1.811

### CRIMPING PINCER

#### Applications

- For installation or removal of ear clamps

**Part No. 39.2382**



### CLAMP ASSORTMENT KIT

#### Features

- Useful assortment of 80 ear clamps and crimping pincer in a durable plastic box
- Sizes from 5/16" to 1"

**Part No. 39.2400**

- Plastic Box

**Part No. 39.2405**

