



Applications

- Ideal for compressed air, water or gas

Features

- For use with natural or synthetic rubber hoses

Specifications

Maximum Working Pressure
150 PSI

Working Temperature
-40°C to 71°C (-40°F to 160°F)



HOSE BARB TO MALE PIPE CONNECTOR (SWIVEL)

Part No.	Hose I.D. in.	Thread (M) NPT in.
33.7128	1/4	1/4
33.7144	3/8	1/4
33.7146	3/8	3/8
33.7154	1/2	1/2



HOSE BARB TO MALE PIPE CONNECTOR (BALL SWIVEL)

Part No.	Hose I.D. in.	Thread (M) NPT in.
33.7628	1/4	1/4
33.7634	5/16	1/4
33.7644	3/8	1/4



HOSE BARB TO FEMALE PIPE CONNECTOR

Part No.	Hose I.D. in.	Thread (F) NPT in.
33.7228	1/4	1/4
33.7234	5/16	1/4
33.7244	3/8	1/4
33.7246	3/8	3/8
33.7254	1/2	1/2




FEMALE TO MALE PIPE CONNECTOR (BALL SWIVEL)

Part No.	Thread (F) NPT in.	Thread (M) NPT in.
33.7728	1/4	1/4



90° SWIVEL ELBOW TO FEMALE PIPE

Part No.	Thread (M) NPT in.	Thread (F) NPT in.
33.7428	1/4	1/4



SWIVEL ELBOW TO MALE PIPE

Part No.	Thread (M) NPT in.	Thread (M) NPT in.
33.7528	1/4	1/4



HEAD PLUG (BALL SWIVEL)

Part No.	Thread (M) NPT in.	Coupler Type
33.7816	1/4	I-1 (1/4" Industrial)
33.7817	1/4	A-1 (1/4" Aro)
33.7818	1/4	T-1 (1/4" Tru-Flate)