

**SAFETY VALVE 1/4" NPT**

Part No.	Pressure Settings (+/- 3%) PSI	Air Flow SCFM	Thread
11.3200	50	47	1/4" (M) NPT
11.3205	70	60	1/4" (M) NPT
11.3210	75	66	1/4" (M) NPT
11.3215	100	96	1/4" (M) NPT
11.3220	115	96	1/4" (M) NPT
11.3230	125	103	1/4" (M) NPT
11.3235	135	120	1/4" (M) NPT
11.3240	140	115	1/4" (M) NPT
11.3250	150	128	1/4" (M) NPT
11.3255	155	137	1/4" (M) NPT
11.3260	163	132	1/4" (M) NPT
11.3270	190	152	1/4" (M) NPT
11.3280	200	160	1/4" (M) NPT

**SAFETY VALVE 3/8" NPT**

Part No.	Pressure Settings (+/- 3%) PSI	Air Flow SCFM	Thread
11.3300	50	47	3/8" (M) NPT
11.3310	75	66	3/8" (M) NPT
11.3320	115	96	3/8" (M) NPT
11.3330	125	103	3/8" (M) NPT
11.3340	140	115	3/8" (M) NPT
11.3350	150	132	3/8" (M) NPT
11.3360	163	132	3/8" (M) NPT
11.3370	190	152	3/8" (M) NPT

**SAFETY VALVE 1/2" NPT**

Part No.	Pressure Settings (+/- 3%) PSI	Air Flow SCFM	Thread
11.3400	40	108	1/2" (M) NPT
11.3405	60	149	1/2" (M) NPT
11.3410	75	189	1/2" (M) NPT
11.3415	100	230	1/2" (M) NPT
11.3420	120	271	1/2" (M) NPT
11.3430	125	281	1/2" (M) NPT
11.3440	140	311	1/2" (M) NPT
11.3450	150	331	1/2" (M) NPT
11.3460	160	352	1/2" (M) NPT
11.3470	180	393	1/2" (M) NPT
11.3480	200	433	1/2" (M) NPT
11.3485	220	474	1/2" (M) NPT
11.3490	235	505	1/2" (M) NPT
11.3495	250	535	1/2" (M) NPT

**IDEAL FOR INDUSTRIAL COMPRESSORS**



**Applications**

- Provides safe pressure control for compressed air tanks

**Features**

- Manufactured under regulations of the "National Board of Boiler and Pressure Vessel Inspectors" in accordance with section VII of the ASME Code covering valves for unfired pressure vessels
- High quality, corrosion resistant, safety valves
- Optimum high-flow discharge rates

**Specifications**

**Pressure Settings**  
 1/4" (M) NPT : 50 PSI to 200 PSI  
 3/8" (M) NPT : 50 PSI to 190 PSI  
 1/2" (M) NPT : 40 PSI to 250 PSI

**Working Temperature**  
 -40°C to 177°C (-40°F to 350°F)

**Construction**  
 Body : Brass  
 Seal : Silicone

**Maximum Installation Torque**  
 100 lb/in.

**Norms**  
 CRN OG-679-C (1/4" and 3/8")  
 CRN OG-2663.1C

